



**TURKUAZ  
KABLO**

# TYPE CODES OF **COPPER INSULATED CABLES**



# TYPE CODES OF COPPER INSULATED CABLES



## A-BCDEFG HxI...JKLMN

### A Basic Types

A- - Outdoor telephone cables  
J- - Installation cables  
AJ- - Outdoor cable with protection against inductive influences  
T- - Terminating cable

### B Insulation Types

O2Y - Cellular PE  
2Y - Solid PE  
O2YS - Foam Skin Insulating cover of cellular PE with additional skin of solid polyolefine.  
Y - PVC  
H - LSZH

### C Filling

F - Petroleum jelly filling  
Blank - Unfilled

### D Screening Material

(St) - Static shield of plastic-backed aluminum Tape for indoor cables  
D - Shield of copper wire whipping over one stranding element (e.g. pair)  
LR - Corrugated aluminium tape  
Blank - No screen

### E Bedding Material

2Y - PE  
Y - PVC  
H - LSZH  
M - Lead Sheath  
MZ - Special Alloyed Lead Sheath  
Blank - No Bedding

### F Armouring Material

b - Armouring  
SR - Corrugated steel tape  
T - Messenger of galvanized steel wires.  
Blank - No Armour

### G Sheath Material

2Y - PE  
Y - PVC  
H - LSZH  
(L)2Y - Laminated sheath (shield of PE coated aluminium tape bonded with PE sheath).  
M - Lead Sheath  
MZ - Special Alloyed Lead Sheath  
Blank - No Sheath

### H Number of Pairs/Quads

2x2 - 2 Pairs  
2x4 - 2 Quads

### I Conductor Size

0.4 - 0.4mm  
0.5 - 0.5mm  
0.6 - 0.6mm  
0.8 - 0.8mm  
0.9 - 0.9mm

### J Stranding Element

PiC - Pairs shielded with copper braid  
PiMF - Pairs shielded with aluminium/polyester tape  
St - Star Quad(Phantom)  
StI - Star Quad(trunk cable)  
StIII - Star Quad (local cable)  
TIC - Triple shielded with copper braid  
TiMF - Triple shielded with aluminium/polyester tape

### K Cable Type

S - Railway signaling cable

### L Types of Stranding

Lg - Stranded in layers  
Bd - Unit Type stranding

### M Copper/Steel Tape/Braid Screen Options

(....Cu) - Total cross section of copper shield in mm sq  
(fK) - Longitudinally applied copper tape, supplement to (St)  
2B...- two layers of steel tape, thickness of steel tape in mm

### N Fire Resistance Options

E30 - 30mins circuit integrity according to DIN VDE 4102 Part 12  
E60 - 60mins circuit integrity according to DIN VDE 4102 Part 12  
F180 - 950°C 180mins Insulation integrity according to IEC 60331&VDE 0427-814